



Overview

LINKS S.r.l. can offer a new generation of machines for a new generation of cosmetic spunlace products. Based on the concept of the double cutting (longitudinal and transversal), we can produce several types of products such as rectangular/square pads, perforated rectangular pads as well as perforated spunlace rolls.

The main difference from the conventional "Punched pads" is that we have 90 degrees angles on the pads and No Waste (skeleton) during the production process.

In some case the waste can be from 3 to 5% if the customer wants to trim the material. In any case far away from the 35% of a standard round pads production.

1979



RC4+ASA+S1 MACHINE

Range of production:

Stacked pads 110x90 mm - 75x75 mm -60x50 mm packed in PE bags

Production:

24 bags/min of 50 pads 110x90 mm.

RC1-LF+SPRP MACHINE

Range of production:

Pads 100x80 mm in loose form in PE bags of 200 units Pads 50x50 mm in loose form in PE bags of 500 units

Production:

12 bags/min of 200 pads 100x80 mm.

Z/API-6S+ASA+S1 MACHINE


Range of production:


Perforated pads 100x90 mm - 75x75 mm - 60x50 mm packed in PE bags

Production:


36-38 bags/min of 50 pads 60x50 mm.

Top View ____





Top View ____



Product Highlights / Options

- √ Several pads dimensions according to the material width.
- √ Embossing on pads surface available.

- √ Material widths from 250 to 630 mm.
 - √ Several perforation steps available.
- √ Stitching on the pad edges.



Technical Layout